



Handmade Leather Bag

by **caracoda** on December 8, 2016

Table of Contents

Handmade Leather Bag	1
Intro: Handmade Leather Bag	2
Step 1: Tools and materials	2
Step 2: Patterns	2
File Downloads	3
Step 3: Cutting the leather	3
Step 4: Preparing the pieces	4
Step 5: Make lace	7
Step 6: Cutting the tooling pattern	8
Step 7: Tooling. Part 1	11
Step 8: Tooling. Part 2	13
Step 9: Tooling. Part 3	14
Step 10: Tooling. Part 4	16
Step 11: Tooling. Part 5	17
Step 12: Oil the leather	19
Step 13: Coloring the background	20
Step 14: Applying antique and finish	22
Step 15: Installing the hardware	26
Step 16: Lacing. Part 1	27
Step 17: Lacing. Part 2	30
Step 18: Lacing. Part 3	32
Step 19: Attaching the strap	35
Step 20: Done!	35
Related Instructables	36
Advertisements	36
Comments	36



Author: caracoda Era Shevtsova

Dare something worthy!

Intro: Handmade Leather Bag

This is an adorable leather bag which is fully handmade from tooling to antiquing to stitching. It makes for a great gift for girls or women, especially hand made by yourself.

The size of the bag is 15cm x 24cm x 8cm. The strap length is 80cm but of course you can make it shorter or longer to your preferences. You will need vegetable tanned leather 3mm thick, although I make these bags from lighter leather, too, and they are still beautiful.



Step 1: Tools and materials

You will need:

Vegetable tanned natural leather

Leather knife, leather punches, lace cutter, lacing needle, rivets and snap button, setter for hardware, Mallet and a set of tooling stamps, edge beveller, D-rings

Antique gel, Professional oil dye (Fiebing's), Carnauba cream, waterproof balm of any type (I like using Obenauf's), Neatsfoot oil, sheep wool, paper towel

Step 2: Patterns


The patterns are included and they are full sized and ready to print. The file is attached in the end of this step. Click it to download it to your computer and then open with an Adobe Reader which you can download for free here:

<https://get.adobe.com/uk/reader/otherversions/>

Any home printer will do the job. You would need to tick the "Tile large pages" option so it is printed in original size at original scale and the "Cut marks" option. Then assemble the printed parts and glue them together connecting the cut marks. Cut the patterns out of paper.

You can also find a lot of different tooling patterns in the internet, I would recommend to check Tandy Leathercraft Library:

<https://www.leathercraftlibrary.com/>



File Downloads





Flora pattern.pdf (1 MB)

[NOTE: When saving, if you see .tmp as the file ext, rename it to 'Flora pattern.pdf']

Step 3: Cutting the leather

First of all we need to transfer the pattern to leather. Place the patterns on leather (leather grain side up). Use a sharp round awl to trace all the lines including marks for hardware installation and lacing holes. When placing the pattern try to use as much workable space on leather as possible so you do not have much waste. This leather is expensive!

Do not press the awl deep into leather; just make light lines to trace the pattern. After tracing all the lines use a very sharp knife or leather scissors to cut out the parts.









Step 4: Preparing the pieces

Now as all the parts are cut out, you need to punch the holes for hardware and lacing and prepare the leather pieces for the next steps.

For lacing holes use a punch with the diameter as big as your lace is wide. If the holes are bigger the lace will be loose and your bag will be flimsy and will fall apart very quick. You want the lace to sit tight in the holes; in this case the construction will be very sturdy and last forever. The punch itself should be sharp. If it keeps being stuck in leather – use a piece of beeswax. First punch the wax and then – leather.

Use a strap end punch or just a scissors to shape the ends of gussets if you want to.

Bevel all the edges so they look smooth and nice. Use the smallest beveller you have (I use #2). Go around the edges on all parts. Use a special curved edger with a hole for tough corners (if you have one).








Step 5: Make lace

Use the same leather to make lace as for the bag itself.

Take a medium sized leather piece and make a 1" hole in the centre. Do not worry if it is not perfect, it does not matter. Start cutting along the edge a couple of millimetres wide. Make a cut half an inch long. This is just so it is easier to start with the lace cutter. Get the cut piece through the cutter (use the widest hole) and start pulling the end of the leather lace carefully. Start cutting slowly, make sure the leather is caught in the blade and goes through it smoothly (it will go smoothly if the blade is sharp). Pull the end of the lace coming from the cutter while holding the cutter steady. Leather will be turning around the cutter freely letting you pull the lace. You can cut approximately 8-9m of lace out of 20cm diameter piece of leather.

If you think the lace is not straight enough or too twisted wet it in the water and wrap around a bottle. Let it fully dry and you have your straightened lace.



Step 6: Cutting the tooling pattern

Attach a few strips of wide sellotape on the back side of leather to prevent stretching and distortion while tooling.

And now it is time for carving or tooling whatever you call it.

We need to case the leather (to get it wet) in order to do this.

Dip the piece of leather you are going to carve in water (just ordinary clean cold water), hold it there for a few seconds and remove. If you are using lightweight leather (1-2mm) then hold it under the water just a couple of seconds. Lay the wet leather down the surface (workbench or table) and leave it for 40-60min depending on leather thickness and room temperature so water can penetrate and spread in the leather evenly. When the leather starts bringing the original color back (getting dry on the surface) and is cold on touch it is ready for carving.

First we need to transfer the design. Place the paper or film with your picture on cased leather and fix it with weight or just tape it with paper tape (be careful with tapes as they leave glue on leather and dye won't stay there).

Use a stylus to trace the lines carefully. Do not apply too much pressure, just enough to leave mark on leather.

Now we need a swivel knife to cut the lines. There is huge assortment of swivel knives in all sizes and types. You will just have to pick one, which sits comfortable in your hand. And just as well there is lots of different sizes and types of blades for these knives. I am using ceramic blade here, quite thick one. The blade must be very sharp.

Now carefully cut the leather following the lines. Hold the knife straight, do not tilt it left or right. Lift the "leading" corner up above the leather surface so it is easier to cut. Do not cut deep, no more than half of the leather thickness otherwise leather won't be strong and lasting in that area.


If you are not confident with using a swivel knife - practice on scrap leather first. Specially, tiny curves – they are the most difficult to master. Once you are confident – go to the bigger project.

Look at the photos and notice as each line fades away on the start and in the end. Apply less pressure and cut shallower in the beginning and in the end of the line to achieve this look. This will give your swivel knife work more pleasant and smooth shape. Avoid cutting through the crossing lines as this will make the carving messy, and look more amateur. See the photos, they are quite self-explanatory.

Now we are ready for the next step







Step 7: Tooling. Part 1

You will also need a mallet. Buy one which is not too heavy for you to work with for a long time. You will also need basic set of stamps for tooling leather. You can find them in the Internet or leather supply shops. We will start with a beveller – a stamp, which pushes leather down on one side of a cut while another side stays raised up. This will give your picture an illusion of volume or 3D look. You will need smaller size for tiny places and larger ones for straight lines.

To use a beveller you place it in the line cut and hit slightly with the mallet. Hit as deep as your cut is. Then move the beveller slightly along the line and hit again. And then move and hit again. Carry on along the all lines. Try to make it smoothly so the prints do not look choppy. Go around all lines. Remember, that you are beveling only one side of the cut line and the other one stays straight up. You can bevel outside the lines or inside the picture. If you bevel inside it is called "inverted" tooling. It has a bit different look, like if the image was pushed in the leather. I am beveling outside the lines.

There will be a frame of some kind here and I would like to emphasize it a little bit. I will do it with this background stamp (see the photos). Then stamp the flower center.








Step 8: Tooling. Part 2

Next we will be lifting flower petals and leaves with a stamp called "lifter" or "undercut". Place it under the concave parts of the petals edges and hit with the mallet. This will make "waves" on the petals and leaves.





Step 9: Tooling. Part 3

Next we will be using a "thumbprint" to add some definition to these petals and leaves. Place it on its heel lifting the other end up above the surface (see the photos). Hit it with the mallet quite deep to get a nice burnished print. Don't forget the leaves.

Center shader will add some texture to the flower center.

Use the veiner on leaves to add more details (see the photos).







Step 10: Tooling. Part 4

Use a camouflage tool to add texture to the stems and a mulefoot for "finishing touch"





Step 11: Tooling. Part 5

Filling background using "bar grounder".

This is a little bit tricky stamp and you would need some practice. If you stamp over the line otherwise it will give messy look (see the photos). Fill up the background nicely little by little.

Now all we have left is a few swivel knife decorative cuts

Do not make many of them, just to add a little touch

Now you can take off the tape, as we do not need it any more.





Step 12: Oil the leather

Carving process makes leather lose oils and we want to restore them. Use Neatsfoot oil or any other leather oil you have or can buy to treat your bag. Give it a thin layer of oil and let it dry completely.





Step 13: Coloring the background

If you cased the leather right and if the leather is of a good quality your carving should give you nice burnishing color in stamp printed areas. But this is not always the case, so we are going to cheat slightly. Well, this is not really cheating but an actual technique used by leathercrafters. We are going to paint the background in dark color to add the desired contrast.

I am using dark brown oil dye. It dries fast and this is what I want.

We will need a soft thin detail brush (I did not have one at hand so trimmed my own from a cheap brush).

Dip the brush into paint and touch the leather in the middle of the area you are going to dye. Do not start near the edges of flower elements as the dye will penetrate leather and mark your flower. Start in center and then move to the edges adding more paint as needed. Make sure you do not miss even very small background areas.

Let it dry completely and then repeat the process but instead of dye use any finish. This will seal the background and let you dye the whole piece without smudging the paints. When using the finish be careful not to drop it anywhere but the background otherwise the antique won't penetrate there and you will get light uncolored spots on your bag.

Now let it completely dry for at least a couple of hours





Step 14: Applying antique and finish

Now you will need antique paste or gel. Use any color you like, my favorite is saddle tan. You will also need a pair of gloves, some clean water in a cup, a piece of sheep wool or sponge and paper towel.

Pour some paint on the piece of wool and start rubbing it in the leather gently in circles. Start with carved area and make sure you did not miss any cuts, get under the petals and leaves, too. Add more paint on wool and carry on in circle movements to cover the entire piece of leather.

Without any delay take a piece of paper towel and wipe off excesses of the antique. If it is already dry wet the towel just slightly and wipe the dry paint off. Do not try to remove all antique from the cuts and grooves, only from the surface. If you are planning to dye the flesh side do it with diluted paint. I usually just dip the piece of wool I just used with excesses of paint on it into water and then smudge it on the flesh side.

Dye all parts of the bag in the same way and don't forget about the shoulder strap and the lace!

Leave it to dry a few hours or better overnight. Then take a piece of wool or linen and polish all parts really well removing all the excesses of paint.


I am going to use carnauba cream as finish. Carnauba cream usually takes off some dye no matter what so do not be alarmed when it happens. You can use just ordinary finish but basically ANY finish will take some dye off anyway.

I put some carnauba cream on sponge and rubbed it gently in circles into leather. It dries quite fast and then I polish leather with a piece of wool to give it nice shine (it does not give gloss though). Note that after carnauba dries out there is no more paint on the sponge. It does not come off any more.

Carnauba cream does not waterproof much and I want my bag to have such property, so I will treat it with waterproofing balm. You can buy one of these in the shoe shop or search Internet for it. There are lots and lots of such product around. I use sponge for application. When using balm try to use one without much wax in it otherwise wax will stuck in the cuts in the carved areas. If such thing happens just let it dry and then use a new and clean toothbrush to brush the wax off (don't use your old toothbrush).

Let the balm absorb into leather and dry completely. Do not forget to treat all parts of the bag including the lace.

When it is dry – polish everything again. Notice the nice shine after polishing.










Step 15: Installing the hardware

Now everything is in color and shiny and we can attach hardware. Install the snap buttons and attach strap D-rings, using rivets.





Step 16: Lacing. Part 1

Now it is time to assemble all the parts.

For lacing you will need a special needle. It is called Jumbo Perma Loc Needle. You actually have to "screw" the lace into this needle. Before you start lacing you need to do one trick. Fold inside the front and back panels to make it easier to lace. Just a little bit so the leather keeps the shape.

Start lacing from the third hole. The gusset will be on top of the panel. Push the needle into the third hole from the grain side of the panel. Pull the lace until you get an inch left.

Push the needle from beneath up to the top through both layers of leather – the panel and the gusset. Now push it through the first hole down.

Pull the needle from beneath to the top through the second hole again and then push it into the third hole. Pull it through the fourth hole from beneath to the top.

Push it down into the fifth hole. Carry on in this manner until you get to the center of the gusset on the bottom of the bag.





Step 17: Lacing. Part 2

When you get there you need to connect the second part of the gusset. Push the needle down through the second part of the gusset and the panel you are lacing. Now pull it through both parts of the gusset to the top.

Lace the gusset and then connect second panel. Pull the needle from beneath through the second panel and the gusset. Carry on lacing in the same direction (opposite to where you started).

When you get to the end and your needle will end up on the grain side push it down through the second hole. Push the needle through between the layers. Pull the lace tight and cut the excess.





Step 18: Lacing. Part 3

Now we repeat the process to lace two other sides. As before, start with the third hole on a panel. Then go through the second hole from underneath to the top through the two layers – the panel and the gusset. Then push the needle down through the first hole. Then go back to the top through the second hole again, and carry on lacing until you get to the middle of the bottom where the gusset parts are connected. Push the needle down through the last available hole.

Now go between the layers.

Then back inside at the other end.

Place the lace between the layers nicely so it is not much visible. Carry on lacing through the remaining holes.

When you get to the edge and your needle ends up on the top push it through the second hole inside the bag. Now push the needle between the layers. Pull the lace tight and cut it off.

I tried to explained as detailed as possible. See the photos, each step is shown clearly. If you still have questions please ask.









Step 19: Attaching the strap

Now we need to attach the strap. Punch the holes for rivets using a small diameter punch (just so the rivet sits tight in the hole) and attach the strap to the D-ring using a rivet.




Step 20: Done!

And we are done!

Good luck and thank you for your time!





Related Instructables



A Leather gift card by grandmaof13



How To Make a Leather Bag by sonofmanuel



Leather Carving Art by fischerworkshops



Simple Leather Purse by solobo



How to make a cowhide Ladies bag by Vaspepe



Leather "Stones" by grandmaof13

Comments

3 comments

[Add Comment](#)



friger says:

OK, printed off the pattern and will start this project on the weekend. Thanks for all the great detail. By the way, is it totally necessary to make the gusset in 2 pieces or was that just for material economy?

Dec 9, 2016. 5:58 AM [REPLY](#)



ClenseYourPallet says:

You are very talented with leather. Thanks for another great project

Dec 8, 2016. 7:49 PM [REPLY](#)



caracoda says:

Thank you!

Dec 8, 2016. 11:46 PM [REPLY](#)